




# EMI Noise Suppression USB 2.0 Cable LNC Series



- EMI Noise Suppression USB2.0 cable
- Flexible ferrite-compound layer
- Provides environment immune to external EMI noise
- Prevents EMI noise emission
- Ideal for ultra high speed clean signal communication
- Transfer rate up to 480Mbps
- Same external diameter as ordinary USB cable
- USB A-B connectors are standard
- Custom connectors available upon request
- Unterminated cable only is available in rolls
- Fire wire cable, VGA cable, Printer cable, LAN cable (RJ45) are also available.

Part Number	Description
LNC-USB2.0-045	USB2.0 Cable $\phi$ 4.5mm L=305 (No connectors)
LNC-USB2.0-045AB-1M	USB2.0 Cable $\phi$ 4.5mm L=1m Terminal Type A-B
LNC-USB2.0-045AB-2M	USB2.0 Cable $\phi$ 4.5mm L=2m Terminal Type A-B
LNC-USB2.0-045AMB-1M	USB2.0 Cable $\phi$ 4.5mm L=1m Terminal Type A-miniB
LNC-USB2.0-045AMB-2M	USB2.0 Cable $\phi$ 4.5mm L=2m Terminal Type A-miniB
LNC-1394-4-4-1M or 2M	Firewire IEEE1394 Cable L=1m or 2m (4-4pin)
LNC-1394-4-6-1M or 2M	Firewire IEEE1394 Cable L=1m or 2m (4-6pin)
LNC-1394-6-6-1M or 2M	Firewire IEEE1394 Cable L=1m or 2m (6-6pin)
LNC-VGA-1M, 2M, 3M, or 5M	Display Cable, VGA Cable L=1m, 2m, 3m, or 5m
LNC-1248-1M, 2M, 3M, or 5M	Printer Cable IEEE1248 L=1m, 2m, 3m, or 5m
LNC-RJ45-1M, 2M, 3M, 5M, or 10M	Cat6 Cable, Ethernet L=1m, 2m, 3m, 5m, or 10m



Also Available:

- Fire Wire Cable
- VGA Cable
- Printer Cable



**KITAGAWA INDUSTRIES America, Inc.**  
2325 Paragon Drive, Suite 10, San Jose, CA 95131  
Tel: (408) 971-2055 Fax: (408) 971-6033  
www.kgs-ind.com

All statements, technical information, and recommendations herein are based on tests and are believed to be reliable, but the accuracy and completeness are not guaranteed and are subject to change without notice due to product improvement and specification change. The following is made in lieu of all warranties, expressed or implied, including the implied warranties of marketability and fitness for purpose. Intermark USA's obligation under this warranty shall be limited to replacement of product that proves to be defective. Before using, user shall determine the suitability of the product for its intended use, and user assumes all risk and liability whatsoever in connection therewith. Intermark USA shall have no liability for any injury, loss or damage arising out of the use of or the inability to use the products. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of seller and manufacturer.

The specifications and properties regarding performance above are not guaranteed, and are subject to change without notice due to product improvement and specification change. While our absorbers are electrically non-conductive, usage directly on the PC Board near the power should be carefully checked. Intermark (USA) Inc. makes no guarantees as to electrical resistivity values and accepts no liability due to short circuits where EMI absorbers are used directly on a PC Board. The products are designed for EMI noise reduction for electronics. This is not recommended to use for applications involving human life or extremely high accuracy. Prior to your usage of the products in production, please verify their performance of EMI noise absorption or adhesive strength of PSA for long term use. Avoid applying any external stress such as bending or high amounts of tension. Note that when the absorber products are cut, bent or pulled, there might be some possibility of creating cracks. For storage of the products keep them in cool and dry rooms at ambient temperature avoiding high temperatures, humidity, and direct sunlight. Keep in a cool, dry, well ventilated place.